

### THIN FILM POROSITY TESTING

#### Complies with the requirements of

AS3894.1-2002 (Wet Sponge Testing); ASTM G62-07; ASTM G6-07; NACE RP0274-2004; NACE SP0188-2006

#### Features

- LED display of voltage
- Internally mounted 9v battery
- Low battery condition LED indicator
- Audible and visual fault alarms
- Telescopic handle for user comfort (extends to 1.2m)
- Large probe head (230 x 40mm) and wider sponge gives faster tests
- Earphone jack to allow testing in noisy

#### Application

- Uses the wet sponge method to detect pinholes in coatings

#### Models

- Selectable 9; 67.5 or 90v test voltage

***We highly recommend that coatings over 150µm, or coatings in corrosive environments, be high voltage porosity tested.***

Made in **AUSTRALIA**



#### Specifications

Range:	0 to 500µm
Operating temperature:	0 to +50°C
Test Voltage:	9, 67.5 and 90V
Telescopic Probe length:	350mm to 1.2m
Power supply:	9v Battery
Dimensions:	210 x 75 x 35mm
Weight:	350g

#### Kit comprises

- Unit and Handle including Sponge
- Belt/pocket clip
- Seven metre earth lead and clip
- Carry case
- Instruction manual with Calibration certificate

PCWI International Pty Ltd

13 Alhambra Avenue CARDIFF NSW 2285  
Ph: (02) 4954 3900 • Fax: (02) 4954 3999  
email: sales@pcwi.com.au • <http://www.pcwi.com.au>

A0104kp